



IMPORTANT! READ ME CAREFULLY.



CHECK OUT OUR **FITTING VIDEOS**

SCAN
HERE



Tools needed : Squeegee (provided), scissors or scalpel blade, masking tape, cleaning solution (methylated spirits or similar NOT white spirit) & lint free cloth.

Precautions : Do not fit in direct sunlight. Clean area thoroughly. Application temperature 7°- 24°C. Do not wash vehicle for 24 hours after fitting.

STEP 1



- ✓ Clean surface where vinyl graphics are being applied.
- ✓ Please use a degreaser to remove any polish or contaminants that may be on the vehicle as this will effect the application of the vinyl.

STEP 2



- ✓ Lay graphic face up on a flat surface and firmly squeegee over graphic to ensure the top paper sheet is adhered to the graphics.
- ✓ Position the graphics using tabs of masking tape and determine the correct position from the proof provided.

STEP 3



- ✓ Once in position, put a strip of masking tape along the top edge of the graphic to form a smooth hinge.
- ✓ For large graphics cut between the spaces to make application easier.

STEP 4



- ✓ Lift the graphic up flat to the surface and carefully peel back the backing paper half way.
- ✓ Please ensure vinyl does NOT come into premature contact with the surface of the vehicle.

STEP 5



- ✓ Holding the graphic slightly away from the surface, use the plastic squeegee supplied to smooth it down removing the backing paper as you go.
- ✓ Work from centre outwards using firm strokes all the way to the bottom.

STEP 6



- ✓ Remove masking tape and then carefully peel back the application paper 180° from the graphic.
- ✓ Any door joins where the graphic goes over will need cutting. Cut centrally in the centre of the gap, open the door and rub down the vinyl edge around the door radius.

REMOVAL OF GRAPHICS

To remove graphics, simply lift edge with fingernail and slowly peel off. **There is no need to use a hot air gun or pressure wash gun as this method will only leave large amounts of adhesive residue.** If there is any adhesive residue remaining, remove using proprietry 'glue and tar' remover solvent.